

TECHNICAL DATA SHEET

Date of issue: 2019

CRAQUELE

DESCRIPTION

Transparent water based one component varnish suitable for decorative effect of craquelé. It makes the final surface through cracks that are created to be like it is old and cracked from time.



TECHNICAL CHARACTERISTICS

Density	: 1.00-1.03 (EAOT EN ISO 2811 20°C)
Viscosity	: 1200-1500 mPas (ASTM D2196-86 25°C)
Thinning	: The product is ready for use and it is applied without dilution
Coverage	: 4 - 8 m ² /lt per layer
Drying time	: Touch dry after 2-4 hours
Packaging	: 750ml
VOC (Volatile Organic Compounds)	: EU limit value for this product Category A: "I", Type:WB, Decorative effect coatings: 200g/l (2010). This product contains max 60g/l VOC.
Painting tools	: Brush Remove as much paint as possible from the equipment in the container and clean it immediately with hot water and soap.
Conditions of application	: Do not apply at temperatures below 10°C and above 35°C.
Storage	: Store at temperatures from 5°C to 40°C. Close the container after every use.



TECHNICAL DATA SHEET

Date of issue: 2019

APPLICATION

Stir well before use

Surfaces must be clean, dry and free from foreign objects and substances.

Apply the surface with a paint in the shade you like and let it dry. This is the base colour of the crackled surface you will create. Then apply a coat of CRAQUELE by brush in one direction only (do not cross or apply twice in the same area). After the surface is dry thoroughly, apply the final coat with a paint in the shade you like. After a few minutes a cracking will appear on the final surface creating the effect of craqueler and the basecoat will start to be obvious through cracks.

The effect of cracking that you create depends on the way the final surface is painted.

HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION

Keep out of reach of children • If medical advice is needed, have product container or label at hand • Do not get in eyes, on skin, or on clothing. • Call a POISON CENTER or doctor/physician if you feel unwell •

Dispose of contents/container in accordance with applicable regional, national and local laws and regulations

It contains: Mixture of 5-chloro-2-methyl-4-isothiazolin-3-one [EC no247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no220-239-6](3:1). May produce an allergic reaction.

Tel. POISON CENTER: 210 7793777